

DT-25N - HiFi Dome Tweeter



















Neodymium hi-fi tweeter, 80 WMAX, 40 WRMS, 8 Ohm

- · Excellent sound characteristics
- Silk soft dome cone with optimised geometry
- Front plate with a specially adapted design
- Very linear reproduction even of lower frequencies
- High efficiency
- Low magnetic dispersion and mechanically very compact due to the application of a high-performance neodymium magnet



- Ideally suited for building smaller speaker systems
- For standing hi-fi speakers of high quality, e.g. in D'Appolito arrangements
- Very fine and natural sound



Technical data

Weight

Impedance (Z) : 8 Ohm
Resonant frequency (fs) : 1,600Hz

Max. frequency range : fx-20,000Hz

Rec. crossover freq. (12 dB) : 1x-20,000Hz

 $\begin{array}{lll} \text{Music power} & : & 80 \text{W}_{\text{MAX}} \\ \text{Power rating} & : & 40 \text{W}_{\text{RMS}} \\ \text{SPL (1 W/m)} & : & 95 \text{dB} \end{array}$

Voice coil diameter : 25mm

Magnet diameter : 33mm

Mounting cutout : Ø 46mm

Mounting depth : 21mm

Dimensions : Ø 66mm

: 70g