CELESTION

LF Loudspeakers

TF0818








- 8in low frequency driver providing 94dB sensitivity and 100Wrms

Frequency Response and Impedance Curves



Topmost curve: Frequency response on axis | Secondary curve: Frequency response at 45° off axis

Power Rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance. Loudspeaker tested in free air.

Continuous Power Rating is defined as 3dB greater than the AES rating.

Sensitivity measured on axis at 1W, 1m in 2 anechoic environment.

General Specifications

Nominal Diameter (mm) 203mm **Power Rating** 100Wrms 4,16 Additional Impedances **Continuous Power Rating** 200W Sensitivity 94dB **Rated Impedance** 8 **Frequency Range** 70-6000Hz 44mm Voice coil diameter (mm) 1.75in Voice coil diameter (in) **Chassis Type** Pressed steel Magnet Type Ferrite Magnet Weight (kg) 0.88kg Magnet Weight (oz) 31oz Voice coil material Round copper **Former Material** Polyimide Cone material Kevlar loaded paper **Surround Material Cloth-sealed** Suspension Single Xmax (mm) 3.5mm Xmax (in) 0.14in Gap Depth (mm) 6mm Gap Depth (in) 0.24in Voice coil winding width 13mm (mm) Voice coil winding width 0.51in (in)

Mounting Information

| Mounting slot dimensions (mm) | 9.5x5.5mm |
|----------------------------------|-------------|
| Mounting slot dimensions | 0.37x0.22in |
| (in) | |
| Mounting slot PCD (mm) | 195-199mm |
| Mounting slot PCD (in) | 7.68-7.83in |
| Number of mounting slots | 4 |
| Overall Diameter (mm) | 208mm |
| overall_diameter_in | 8.19in |
| Overall Depth (mm) | 99mm |
| Overall Depth (in) | 3.5in |
| Cut-out Diameter (mm) | 183mm |
| Cut-out Diameter (in) | 7.2in |

Small Signal Parameters

Xmax is derived from: (voice coil winding width-gap depth)/2.

Small Signal Parameters are measured after unit subjected to pre-conditioning signal.

| Sd | 226.98cm2 / 35.18in2 |
|--------------|----------------------|
| Fs | 100.00Hz |
| Mms | 19.57g / 0.69oz |
| Qms | 3.311 |
| Qes | 0.493 |
| Qts | 0.429 |
| Re | 6.72 |
| Vas | 9.44I / 0.33ft3 |
| Bi | 12.95Tm |
| Cms | 0.13mm/N |
| Rms | 3.72kg/s |
| Le (at 1kHz) | 0.75mH |
| | |

Packed Dimensions & Weight

| Unit Weight (kg) | 2.3kg |
|---------------------------|--------------------------|
| Unit Weight (lb) | 5.1lb |
| Single pack size W x D x | 230mm x 230mm x 110mm |
| H (mm) | |
| Single pack size W x D x | 9.1in x 9.1in x 4.3in |
| H (in) | |
| Single pack weight (kg) | 2.8kg |
| Single pack weight (lb) | 6.2lb |
| Multi Pack Qty | 140 |
| Multi pack size W x D x H | 42.1in x 33.5in x 33.9in |
| (in) | |
| Multi pack weight (kg) | 350kg |
| Multi pack weight (lb) | 770lb |
| | |



Celestion, Claydon Business Park, Great Blakenham, Ipswich, IP6 0NL United Kingdom

