



SPH-30X/8SW

3 50W

Order No.: 0104190

PRODUCTINFOS

High-quality hi-fi full range speakers, 20 W, 8 Ω (/8) or 4 Ω (/4), with black Kevlar cone

- Well-damped Kevlar cone of extra low weight
- Drive system with full air ventilation
- High-quality neodymium magnet system with double magnet
- Specially developed basket also for multiple arrangements
- High efficiency
- Small speakers for background PA applications or e.g. rear speakers in home cinema systems

105 Hz

• Suitable for applications from mid-high range speakers or full range midrange speakers in high-end hi-fi speaker systems to multiple arrangements in column speakers

TECHNICAL SPECIFICATIONS

SPH-30X/8SW

Impedance (Z) 8 Ω

Frequency range f3-17,000 Hz

Resonant frequency (fs)



SPH-30X/8SW

Eff. cone area (Sd)

Power rating (RMS) 20 W
Peak music power output (MAX) 50 W

SPL 87 dB/W/m Suspension compl. (Cms) 0.90 mm/N

Moving mass (Mms) 2.65 g Mech. Q factor (Qms) 8.59 Electr. Q factor (Qes) 0.49 Total Q factor (Qts) 0.42 Equivalent volume (Vas) 1.3 l 5.7 Ω DC resistance (Re) Force factor (BxL) 4.48 Tm Voice coil induct. (Le) 0.5 mH Voice coil diameter Ø 21 mm Voice coil former Kapton Linear excursion (X_{MAX}) ± 2 mm

Magnet weight neodymium

Mounting cutout Ø 73 mm

Mounting depth 40.7 mm

Dimensions Ø 80.5 mm x 42 mm

30 cm²

Width 80.5 mm 80.5 mm Height Depth 42 mm Colour black Admiss. ambient temp. 0-40 °C Weight 141 g Packing unit 1 3" Type of speaker

Packing dimensions (W x H x L) 0.085 x 0.06 x 0.085 m

Gross weight 0.177 kg
Net weight 0.141 kg

SPH-30X/ dB Ω 80 100 60 90 40 80 20 70

1k

2k

5k

10k

20k

500

200

50

100

