



HT-88

Order No.: 0103170

PRODUCTINFOS

PA horn tweeter, 50 W, 8 Ω

- Very linear and wide bandwidth radiation
- High efficiency
- Ferrofluid-cooled and ferrofluid-vaporised

TECHNICAL SPECIFICATIONS


HT-88

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	fx-18 kHz
Resonant frequency (fs)	2.5 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	4 kHz
Power rating (RMS)	50 W
Peak music power output (MAX)	100 W

HT-88

SPL	99 dB/W/m
Voice coil diameter	Ø 25 mm
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 82 mm
Mounting depth	75 mm
Hole spacing X-axis	67 mm
Hole spacing Y-axis	67 mm
Dimensions	87 x 87 x 75 mm
Width	87 mm
Height	87 mm
Depth	75 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.67 kg
Packing unit	1
Packing dimensions (W x H x L)	0.09 x 0.085 x 0.09 m
Gross weight	0.71 kg
Net weight	0.67 kg

HT-88 (10.3170)



HT-88

