



SPM-205/8



Order No.: 0105390

PRODUCTINFOS

Hi-fi bass-midrange speakers, 70 W, 8 Ω (/8) and 4 Ω (/4)

- Excellent replacement speakers of the same quality as from the original equipment manufacturer
- Coated low-resonance paper cone
- Long-term stable rubber surround
- To be used preferably in closed or transmission line cabinets

TECHNICAL SPECIFICATIONS

SPM-205/8

Impedance (Z)	8 Ω
Frequency range	f3-5,000 Hz
Resonant frequency (fs)	37 Hz
Power rating (RMS)	70 W
Peak music power output (MAX)	150 W
SPL	89 dB/W/m
Suspension compl. (Cms)	0.75 mm/N



SPM-205/8

Moving mass (Mms) 22 g Mech. Q factor (Qms) 2.95 Electr. Q factor (Qes) 0.92 Total Q factor (Qts) 0.7 54 I Equivalent volume (Vas) DC resistance (Re) 7.2 Ω Force factor (BxL) 6.50 Tm Voice coil induct. (Le) 0.7 mH Voice coil diameter Ø 25.5 mm Voice coil former aluminium Linear excursion (X_{MAX}) ± 3 mm Eff. cone area (Sd) 210 cm² 380 g Magnet weight Magnet diameter Ø 80 mm Mounting cutout Ø 183 mm Mounting depth 80 mm Mounting hole diameter Ø 216 mm

Dimensions Ø 200 mm x 88 mm

Outside diameter Ø 200 mm Width Ø 200 mm Depth 88 mm black Colour Admiss. ambient temp. 0-40 °C Weight 1.4 kg Packing unit 1 Type of speaker 8"

Packing dimensions (W x H x L) $0.215 \times 0.125 \times 0.215 \text{ m}$

Gross weight 1.5 kg
Net weight 1.4 kg

SPM-205/8 (10.5390) dB Ω



