

# Specifications

## SPECIFICATIONS

BELOW ARE THE 2020 PARAMETERS, MEASURED ACCORDING TO THE AES2-1984-R2003 STANDARD.

<b>Sensitivity (2,83V/1m) :</b>	<b>97,7dB</b>
<b>Sensitivity (1W/1m) :</b>	<b>96,8 dB</b>
<b>Bandwidth :</b>	<b>40Hz-20KHz</b>
<b>Impedance :</b>	<b>8 <math>\Omega</math></b>

<b>Surround :</b>	<b>3 plies paper</b>
<b>linear excursion :</b>	<b>+/- 2,3 mm</b>
<b>Magnet:</b>	<b>ferrite 120mm</b>
<b>Fields Strength :</b>	<b>1,25 T</b>
<b>Frame:</b>	<b>Aluminum</b>
<b>Driver diameter:</b>	<b>224/237mm</b>
<b>Fixing holes diameter :</b>	<b>224mm</b>
<b>Baffle opening :</b>	<b>212mm</b>
<b>Driver depth :</b>	<b>100mm</b>
<b>Driver weight :</b>	<b>2,3 kg</b>

<b>Fs :</b>	<b>57 Hz</b>
<b>Re :</b>	<b>6,5 <math>\Omega</math></b>
<b>Le 1 kHz :</b>	<b>0,43 mH</b>
<b>Qts :</b>	<b>0,46</b>
<b>Qes :</b>	<b>0,53</b>
<b>Qms :</b>	<b>7,6</b>
<b>Vas :</b>	<b>80 L</b>
<b>Bl :</b>	<b>6,48</b>
<b>Mms :</b>	<b>8,9 g</b>
<b>Sd :</b>	<b>254,5cm<sup>2</sup></b>